



## **Technical Data Sheet**

## PRS<sup>4</sup> Passive HDMI Cable



## Designed for high performance applications

Kordz PRS $^4$  Passive HDMI Cables are designed to meet the high demands and rigour of professional integration. The Kordz PRS $^4$  range features cables that are compact, tough and flexible with a 2kg retention force die-cast connector. Kordz PRS $^4$  HDMI Passive Cables support the full features and benefits of the latest HDMI technology when using 4K HFR or 8K devices.


- · Ultra High Speed certified
- 48Gbps support for 8K/10K, HDR, VRR, HFR, 3D, FRL
- Robust engineering and construction with premium materials
- 15µ" gold-plated solid copper pins
- · Compact connector with full internal zinc-alloy diecast housing
- Easy installation aided by the unique Kordz shark-nose dust-cap
- · Convenient easy tear bulk packaging minimising waste on site
- · UL CMG rating
- · High contrast detailed labelling with inventory management design
- · Backed by the Kordz Lifetime Guarantee





Technical Specifications		Reference Standards:		
HDMI Cable Certification		0.5m to 5.0m Lengths		
HDMI CTS (Certified Test Specific	cations)	Ultra High Speed HDMI® Cable		
Certified Data Rate		12.0Gbpsc, 48Gbps agg		
Supported Data Rate		≥12.0Gbpsc, 48Gbps agg (8K UHD)		
HDMI Clock		1200MHz		
Construction				
Primary Conductors		Solid 30-26 AWG OFC, length dependent		
Insulation	FRL/TMDS Pairs	Polyethylene		
	4C + HEAC Pairs	HDPE / Polyethylene		
Shielding	FRL/TMDS Pairs	AL/Mylar, 100% Coverage with 25% Overlapping		
	Overall	AL/Mylar, 125% Coverage + Tinned copper braid, min 85% coverage		
Cable Jacket Material		UL CMG fire-rated PVC composite materials		
HDMI Connector Shell		Anti-fatigue die cast Zn alloy, 1µ" 24K Gold plated		
HDMI Connector Pins		Solid OFC, 15µ" 24K Gold plated		
Termination		High frequency soldering		
HDMI Back-shell		ABS front shell with PVC injection moulded boot and strain relief		
Mechanical				
Cable Diameter	0.5m - 3.0m	30 AWG 6.0mm   0.24in Ø		
	4.0m - 5.0m	26 AWG 8.0mm   0.31in Ø		
Mounting Depth		Cable gauge dependent (see below)		
Cable Bend Radius	0.5m - 3.0m	30.0mm   1.18in		
	4.0m - 5.0m	40.0mm   1.57in		

Part No	Length	AWG	Technology	Inner Ctn Qty	Master Ctn Qty
K36426-0050-CH	0.5m   1' 8"	30	Passive	15	90
K36426-0100-CH	1.0m   3' 3"	30	Passive	12	72
K36426-0150-CH	1.5m   4' 11"	30	Passive	10	60
K36426-0200-CH	2.0m   6' 6"	30	Passive	8	48
K36426-0300-CH	3.0m   9' 10"	30	Passive	6	36
K36426-0400-CH	4.0m   13' 1"	26	Passive	8	24
K36426-0500-CH	5.0m   16' 4"	26	Passive	6	18



Kordz products are sold with a limited warranty as outlined at: www.kordz.com @2021 Kordz International. All rights reserved. Kordz Connectivity. Assured & Kordz range logos are trademarks or registered trademarks of Kordz International in Hong Kong and in other countries. All other trademarks are the property of their respective owners.