

Description: Solar Cable TÜV Approved H1Z2Z2-K
Double Insulated LSNH Black/Red
4.0mm² - 6.0mm²



Product Construction

Conductor Material	:	Tinned Copper
Conductor Stranding	:	Class 5 to BS EN 60228
Insulation Material 1	:	Low Smoke Non-Halogen (LSNH)
Insulation Colour 1	:	Black
Insulation Material 2	:	Low Smoke Non-Halogen (LSNH)
Insulation Colour 2	:	Red

Mechanical Characteristics

Overall Diameter	:	See Table Below
Temperature Range Fixed	:	-40°C to +90°C
Max. Conductor Temperature	:	+120°C (for 20,000 hours)
Min. Bend Radius	:	5 x Overall Diameter
Weight	:	See Table Below

Electrical Characteristics

Inner Conductor DC Resistance	:	See Table Below
Nominal Voltage Rating	:	1.0 kV (AC), 1.5 kV (DC)
Max. Permitted Voltage	:	1.8 kV (DC)
Test Voltage	:	6.5 kV (DC)

Certifications & Standards

Manufactured in accordance	:	EN 50618
Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
Water Resistance	:	AD8 to EN 50525-2-21 "Annex E"
Insulation Resistance	:	EN 50618 Table 2
Cold Resistance	:	EN 50618 Table 2
Acid & Alkaline Resistance	:	EN 50618:2014 Annex B
TÜV Approved	:	Yes
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CE CPR Classification	:	Dca s2, d2, a1 to EN 50575:2014+A1:2016



Part No.	Size mm ²	Weight kg/km	OD mm	Conductor Resistance Ω/km	Current Carrying Capacity in Free Air @ 60°C	Current Carrying Capacity on Surfaces @ 60°C
050002D-RED	4.0	56	5.4	5.09	55A	52A
050003D-RED	6.0	76	6.2	3.39	70A	67A



Publication Date: 31/01/2023
Revision Number: 2.0
Written by: GB
Authorised by: GB

This technical document and its information and images are intended for guidance only. Due to technical improvements, manufacturing changes or commercial factors the product may vary, and we reserve the right without notice or liability to amend the product information.