



Qing Cables



T: 01242 224141


F: 01242 224134

www.qingcables.com

enquire@qingcables.co.uk

This specification and images

© Qing Cables Ltd



Twin & Multicore Speaker Flex LSZH Sheath

Oxygen Free Copper Professional Installation Speaker Flex

(Copper Purity 99.9999%)

LSZH Sheath to IEC60332-1 / IEC60754 / IEC61034

Qing Cables OFC "QCSound" Cable range uses the highest quality oxygen free copper to deliver optimum performance to compliment the best Hi-Fi and Home Cinema systems.

The Twin/Multicore range are also ideal for fixed installations, or use in Studio's.

Physical Characteristics

	QCS025/2 LSZH	QCS025/4 LSZH	QCS040/2 LSZH
	2.50mm ²	2.50mm ²	4.00mm ²
Conductor:	Stranded Pure Copper		Stranded Pure Copper
Size:	50/0.25mm		56/0.30mm
Nº of Cores:	2 Cores	4 Cores	2 Cores
Insulation:	LSZH Ø3.00mm		LSZH Ø4.20mm
Filler:	Chalk		Chalk
LSZH Outer Sheath:	Ø7.50mm	Ø10.0mm	Ø11.0
Sheath Colours	Black		Black
EN50575 CPR Class:	E _{ca}		E _{ca}
CIBSE TM65 Embodied Carbon [kgCO ₂ e/1000m]	480		754
Weight	90kg/KM	175kg/KM	160kg/KM

LSZH Sheath meets:
IEC60332-1 [Flame Propagation]
IEC60754 [Halogen Free]
IEC61034 [Smoke Emissions]

Electrical Characteristics

Conductor DC Resistance	<8.0 [Ω/km]	<5.0 [Ω/km]
Rated Temperature	-20°C → 80°C	-20°C → 80°C
Operating Voltage	450/750V	450/750V
Test Voltage	2000V	2000V
Insulation Resistance	>500 [MΩ/km]	>500 [MΩ/km]
Minimum Bending Radius	5x Diameter	5x Diameter

Colour Code

Core 1	Blue	Blue	Blue
Core 2	Red	Red	Red
Core 3		Green	
Core 4		Yellow	

Our full product range includes:

COAXIALS: RG / URM Digital / Satellite (incl Sky+) [CAI Approved] CCTV RF / Microwave
TELECOM: CW1308LSF CW1308LSZH CW1308B CW1128 CW1128/1198 CW1128/1252 Dropwire Jumper Wire CW1311 3002 Coax Flat Cordage
STRUCTURED WIRING: CAT5e UTP & FTP CAT6 UTP & FTP CAT6A U-UTP & U-FTP CAT7A S-FTP [PVC LSZH External UV PE SWA Versions]
DATA: Single Pair Shielded/Unshielded Overall Shielded Core Overall Shielded Pairs Foil & Braid Shield Individual Shielded Pairs Twinax [Belden Equivalents]
DEF STANDARD: 7/0.2 Unscreened / Screened 16/0.2 Unscreened / Screened
CCTV / SECURITY: RG/URM Coaxial Video/Door Entry Composites BS4737 Alarm Flex Mains Flex PH30/PH120 Fire Performance Cable
FIBRE OPTICS: Singlemode/Multimode Loose Tube/Tight Buffer Internal/External LSZH Corrugated Armour/SWA
SPEAKER FLEX: "QCSound" Pro Grade OFC Cores LSZH Sheaths External Grade
CONNECTED HOME: QCMCS [2x HDTV Coax] + [2x CAT6] + [1x CAT5e]
CONTROL BUS CABLES: KNX/EIB Bus Cables DataBus® DiviceNet™ PROFIBUS Lutron Grafik Eye® CRESSNET® SIMMTRONIC - EBUS / MBUS / OBUS Echelon LonWorks® Mode Lighting
MAINS FLEX: H03VV-F H03VVH2-F H05VV-F H05Z1Z1-F BS6500/BS7919 Arctic Grade H07RN-F
SOLAR: TUV Approved PV Cable.

All our products are RoHS2 [2015/863] and REACH Compliant unless stated otherwise.

Every care is taken to ensure all information contained in this publication is correct.

No legal responsibility can be accepted for any inaccuracy.

The company reserves the right to alter or modify the information without notice.

Any images are for illustration purposes only.

Registered in England & Wales No. 2181405 Directors: M.L.G.Taylor, L.J.Taylor, K.M.Wyld

Statement of Conformance

It is hereby certified that any goods supplied that reference those above, conform to this specification unless otherwise noted

[Signature]