
Corning Cabelcon

New CX3 SpringConnect™ Connector with Class A+ shielding and permanent continuity!



SpringConnect[™] for safe use on all F-ports



Total pull strength exceeds 3 kg before it disconnects



Reliable and secure modem connections. Easy to push on. Superb screening efficiency.



The new CX3 Spring Connect™ keeps continuity and remains RF tight until it's completely disconnected.



CX3 SpringConnect™ is waterproof with our additional Seal Ring Item no. 99900902



CX3 SpringConnect™ is also available as ready made jumper cables for modems and other applications in customer specified lengths.

Cabelcon presents the new CX3 SpringConnect™ F-connector with excellent mechanical and electrical specifications. Most ordinary push-on connectors have weak pull-off strength and poor screening capabilities resulting in egress/ingress problems.

The new CX3 SpringConnect™ is different

Corning Cabelcon's new CX3 SpringConnect[™] comes with Cabelcon's unique Nitin-6[™] plated Secure Spring Technology. The CX3 SpringConnect[™] is safe to use for all regular CATV installations, modem cables, satellite receiver installations and other set-top boxes.

The typical disconnect pull-off value from the F-port is more than 3 kg. The continuity is effectively secured and SpringConnect™ remains RF-tight until it's completely disconnected.

The CX3 SpringConnect™ is already approved by the largest cable operators in Europe.



Technical Data CX3 3.9 (Typical)

Operational to 3 GHz

Impedance 75 Ohm Shielding Efficiency 30 - 1000 MHz >100 dB Transfer Impedance 5-30 MHz <2.5mOhm/mtr Return loss 0.5 – 1000 MHz (typ) 45 dB Return loss 1000 – 3000 MHz (typ) 40 dB IMD (3rd order@2x500mW) -152 dBc IMD (IP3 value) +103 dBm AMP rating cable data Max. Tensile strength (overall) 300 N Waterproof 1 meter/24 hours with additional Seal Ring!

Detailed datasheets available on request

Ordering information

F SC-59-CX3 3.9 Short Item no. 99909523 F SC-56-CX3 4.9 Short Item no. 99909549 F SC-56-CX3 5.1 Short Item no. 99909553 CX3 SpringConnect™ jumper cables are available in various lengths. Please contact our Customer Service for more information on item numbers etc.

