

## Technical specifications : Ref. 719504

|                                |      |                 |
|--------------------------------|------|-----------------|
| Number of inputs               |      | 5               |
| Number of cascable outputs     |      | 5               |
| Number of user outputs         |      | 8               |
| Frequency range TERR.          | MHz  | 88 ... 862      |
| Frequency range SAT.           | MHz  | 950 ... 2400    |
| Input level TERR.              | dBmV | 0.08 ... 0.11   |
| Input level SAT.               | dBmV | 0.065 ... 0.112 |
| Through losses TERR.           | dB   | < 4             |
| Through losses SAT.            | dB   | 2 ... 3.5       |
| Tap losses TERR. Active        | dB   | 0 ... 4         |
| Tap losses TERR. Passive       | dB   | 32              |
| Tap losses SAT. HG             | dB   | 2 ... 7         |
| Tap losses SAT. LG             | dB   | 12 ... 14       |
| Output level 10Ch DVB-T        | dBmV | 0.078           |
| Isolation H/V                  | dB   | > 50            |
| Isolation users                | dB   | > 30            |
| Powering                       | Vdc  | 12 ... 18       |
| Max. current (PSU - TERR ACT.) | mA   | 115             |
| Max. current (PSU - TERR PAS.) | mA   | 5               |
| Max. current (STB)             | mA   | 85              |
| Operating temperature          | °F   | 23 ... 113      |
| Protection index               |      | 20              |