TRIAX

connecting the future



TOS-Cab32 Fibre Distribution Cabinet

Article number: 307911

Product description:

Distribution box for TRIAX PLC splitters TOS xxSC, splice trays, layout pigtails to match trunk and drop fibre cables.

Can be used as fibre optic terminations of optic access network or sub-distribution points in and outdoor.

- Plastic enclousure, flame retardant, againg and UV resistant.
- Special screw and key for its door lock
- Mounting on wall or on pole
- Bi-layer structure of the box: bottem for splicing and upper layer for splitting and distribution
- Special lock device for outlet of drop cables
- 2 standard slots for TOS xxSC PLC splitter cassettes--> max splitting factor: 32

Specifications

ORDER INFORMATION	
EAN Number	5702663079113
CHARACTERISTICS	
Туре	TOS-Cab32

08/04/2021, 09:23

Place of Usage	Splitter cassettes: 2 x 1:16 or 4 x 1:8 + 2 x splice trays
OPERATIONAL	
IP Housing protection class	IP 65
Temperature - operating	-40+80 °C
Temperature - storage	-40+80 °C
MECHANICAL	
Main material	Plastic
Colour	RAL 7035 - Light grey
Product Height	410 mm
Product Width	345 mm
Product Depth	130 mm
Packaging Height	0,350 m
Packaging Width	0,420 m
Packaging Depth	0,143 m
Packaging Volume	0,021 m3
Net Weight	2,230 kg
Tara Weight	0,160 kg
Total Weight	2,390 kg

2 of 2