A Solutions

MS-TestPro

USB Cable Test Module (UCT) Optional Module

The MSolutions USB cable test module allows for integrators to gain a deeper understanding of their USB connectivity through qualification of the cabling used within installations. The tester allows for the DC measurement of the internal wiring. Determine the USB-C features, USB2.0 (480Mbps), USB3.1 (Gen1 up to 5Gbps), USB3.1 (Gen2 up to 10Gbps), charging, monitor/laptop power, audio support, video and quality.

The module has the capability of providing accurate test measurements for the following USB cable types: USB-C to USB-C connections, USB-C to USB3.0 (Type A) connections, USB3.0 (Type B) to USB3.0 (Type A) connections. The tester will identify and qualify the USB version that he cable has been manufactured to (i.e. 1.0, 1.1, 2.0, 3.0, DP, ETH)

The module has the capability to measure the power consumption of a USB device by connecting the module between the USB device and the Host - which will allow for the user to view the power draw by the device from the Host.



CHDBT

- Expansion module for the MS-TestPro 104B
- Adds capability for USB Cable testing on the MS-TestPro MS-104B
- Tests for passive USB cabling data speeds, compliance and power •
- Quick, simplified USB cable troubleshooting
- Expands testing coverage for integrators save time and money
- Fast report generation in .pdf format

Specifications:

Key Features:

- UCT module dimensions (W x D x H): 60mm x TBCmm x 25mm
- UCT module weight: 0.2kg
- Operating temperature: 32°F to 104°F (0°C to 40°C)
- Storage temperature: -4°F to 140°F (-20°C to 60°C)
- Operating humidity: 0-80% non condensing

Package Contents:

1x USB Cable Test module (UCT)



12:03 (°j)	USB-C T	ester 🛆 🔗 Ne Tester	99%	12:03 (f
Max power	consumption	= 0.000 (W)		Support
V _{BUS}		USB 2.0/		
5.0		V _{BUS} = 4		USB Pow
4.8	~~~			USB Pow
4.5				USB 3.0/
0	10	20	30 s	Alternate
				Debug A
I _{USB}	I _{USB} max = 0.0001 (A) I _{USB} = 0.000 (A)			Audio Ad
0.3				
0			_	
-0.3 0	10	20	 30 s	
Start Log		Test(s)		
-	_	_	_	

1/3.2

