

**KNX 2pair 0.8mm Screened White LSNH**

**Part Number:** 350303E-LSNH-WHT

**Description:** KNX 2pair 0.8mm Screened White LSNH

**Product Construction**

Conductor Material	:	Bare Copper
Conductor Stranding	:	Solid, 1/0.80mm
Insulation Material	:	Polyethylene (PE)
Number of Pairs	:	2
Colour Code	:	Black, Red; Yellow, White
Drain Wire	:	Tinned Copper, 1/0.40mm
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	White

**Mechanical Characteristics**

Overall Diameter	:	6.6mm ± 0.35mm
Temperature Range	Fixed :	-20°C to +70°C
	Flexing :	0°C to +70°C
Bend Radius	:	10 x Overall Diameter
Weight	:	52 kg/km

**Electrical Characteristics**

Max. Conductor DC Resistance @ 20°C	:	≤ 36.6 Ω/km
Capacitance, Data	Core to Core :	52 pF/m ± 10
	Core to Screen :	104 pF/m ± 20
Impedance	:	92 Ω ± 10
Insulation Resistance @ 20°C	:	≥ 200 MΩ*M
Voltage Rating	:	300/500V

**Certifications & Standards**

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
CPR Classification	:	Eca to EN 50575:2014+A1:2016

