

WEB 16/22 White Blind Control LSNH



Part Number: 390151E-LSNH-WHT
Description: WEB 16/22 White 1pair 22awg
 Screened + 1pair 16awg LSNH White

Product Construction

Alternative to Lutron	:	QSH-CBL-M-500
Data		
Conductor Material	:	Bare Copper
Conductor Stranding	:	22awg, 16/0.16mm
Insulation Material	:	Foamed Polyethylene (FPE)
Number of Pairs	:	1
Drain Wire	:	Tinned Copper, 24awg
Screening 1	:	Overall Aluminium Foil
Screening 1 Coverage	:	>100%
Core Colours	:	White, Violet

Power

Conductor Material	:	Bare Copper
Conductor Stranding	:	16awg, 26/0.25mm
Insulation Material	:	Polyethylene (PE)
Number of Cores	:	2
Core Colours	:	Black, Red

Overall Construction

Sheath Material	:	Low Smoke Non-Halogen (LSNH)
Sheath Colour	:	White

Mechanical Characteristics

Overall Diameter	:	6.2mm ± 0.2mm
Temperature Range	Fixed	: -20°C to +70°C
	Flexing	: 0°C to +60°C
Bend Radius	:	10 x Overall Diameter
Weight	:	69 kg/km

Electrical Characteristics

Max. Conductor DC Resistance @ 20°C	: Data	≤ 55.4 Ω/km
	: Power	≤ 13.7 Ω/km
Capacitance, Data	Core to Core	: 50 pF/m ± 10
	Core to Screen	: 100 pF/m ± 20
Insulation Resistance @ 20°C	:	≥ 5000 MΩ*Km
Voltage Rating	:	300/300V

Certifications & Standards

Flame Retardancy	:	BS EN 60332-1-2
Low Smoke	:	BS EN 61034-2
Halogen Gas	:	BS EN 60754-1&2
RoHS 3 Compliant	:	Yes
REACH Compliant	:	Yes
UKCA CPR Classification	:	Eca to BS EN 50575:2014+A1:2016

